

# MICROTORCHES

NEW



## item: 214/00 - MICROTORCH K2000

(quantity discount)

### TECHNICAL FEATURES:

Lighting:	piezoelectric
Gas lasting:	20-25 minutes
Flame temperature:	1300° C
Type of gas:	butane/ propane
Weight:	213 gr



## item: 219/00 - MICROTORCH GT-3000S

(quantity discount)

### TECHNICAL FEATURES:

Lighting:	piezoelectric
Gas lasting:	20-25 minutes
Flame temperature:	1300° C
Type of gas:	butane/ propane
Weight:	250 gr



## item: 229/00 - MICROTORCH PT-4000

(quantity discount)

### TECHNICAL FEATURES:

Lighting:	piezoelectric
Gas lasting:	20-25 minutes
Flame temperature:	1300° C
Type of gas:	butane/ propane
Weight:	100 gr



## item: 218/00 - MAXITORCH EXPERT 27

(quantity discount)

### TECHNICAL FEATURES:

Lighting:	piezoelectric
Gas lasting:	20-25 minutes
Flame temperature:	1300° C
Type of gas:	butane/ propane
Weight:	380 gr



## item: 219/01 - GAS REFILLING BOMB

Spare gas refilling for Micro-torches EXPERT 27, GT 3000S and PT 4000.

## INDUCTION BUNSEN



**item: 213/00 - INDUCTION BUNSEN iLab**

Bunsen electronic induction to operate with ease and precision. An instrument of innovative work that looks at your security. The burner heats the spatula in less than two seconds, a sensor located above the chamber for the induction detects the presence and activates the heating phase, as well as the stops when you move away from the work area. Instant heating of the instrument. Precise and safe, for without flame. Induction technology.

## BUNSEN



Autobunsen, electronic burner with safety thermo-couple, available with natural gas and propane gas.

**item: 225/00 - AUTOBUNSEN ELECTRONIC, natural gas**

**item: 226/00 - AUTOBUNSEN ELECTRONIC, propane gas**



If The safety bunsen burner is built up in order to follow up all safety standards. This is equipped with safety thermo-couple to stop the gas exit, in case of accidently flame, lighting off.

**item: 215/00 - SICURBUNSEN, natural gas**

**item: 216/00 - SICURBUNSEN, propane gas**



Bunsen burner, with pilot light, available with natural gas and propane gas.

**item: 200/00 - BUNSEN, natural gas**

**item: 210/00 - BUNSEN, propane gas**

## LABORATORY VIBRATORS



Laboratory Vibrators SHAKER guarantee a notable power changeable by means of an electronic, circuit and anti-trouble filter.

They have a removable rubber surface with counter-sink edges for an easy cleaning even with steam (high thermic and mechanical resistance of the materials). Our Vibrators guarantee an high noiseless and steadiness by means of the perfect vertical movement, deadened by four little feet of soft mousse.

**item: 722/00 - SHAKER 2**

**item: 724/00 - SHAKER 4**

**item: 726/00 - SHAKER 6**

TECHNICAL FEATURES:	SHAKER 2	SHAKER 4	SHAKER 6
N° cylinders:	2	4	6
Overall size:	14,5x16,5x8,5 cm	16x25x10 cm	36x26x13 cm
Useful work plane:	13x15 cm	15x23 cm	34x24 cm
Absorption:	120 Watt	150 Watt	400 Watt
Feeding:	230V/50 Hz	230V/50 Hz	230V/50 Hz
Weight:	3 Kg	4,8 Kg	10 Kg

## STEAM CLEANER



**item: 710/00 - CLEANER 150**

3.5 bar-steam generator for the decontamination and cleaning of metals, ceramic, resins, etc. The boiler has a capacity of 5 litres and is completely made from robotized welded AISI stainless steel. The latest model offers innovative solutions that guarantee years of reliable performance with minimum maintenance required. The steam gun is thermoinsulating and has four different nozzles. The steam ejection function is pedal-operated, against accidental electrocution caused by humidity. Constructed and tested in compliance with EC norms.

TECHNICAL FEATURES:	
Working pressure:	3,5 bar
Heater capacity:	5 lt
Sizes:	22x34x40 cm
Weight:	12 Kg

## CIRCULAR SAW



**item: 700/00 - CIRCULAR SAW**

This saw has been designed to cut any kind of pattern out of plaster with the up most precision. It guarantees maximum safety to the operator while he's using it. All controls run on low voltage and protected (IP54) with appropriate devices against humidity and dust. The magnetic table guarantees excellent stability of the base plate and pattern stand, that can be slanted and locked an any position.

The diamond tipped disc combines a specular finish with a considerable cutting depth. A suction unit should be connected (to the coupling on the back) to ensure correct operation.

**item: 700/20 - Modeltray Accu-trac**

**item: 700/21 - Diamond disc Ø 80x0,2 mm**

TECHNICAL FEATURES:	
Feeding:	230 V - Hz 50/60
Motor power:	60 Watt
Speed:	2.800 g/m
Diamond disc:	Ø 80x0,2 mm
Weight:	10 Kg

## WORKING CHAIR



### item: 594/00 - WORKING CHAIR

Working chair with:

#### TECHNICAL FEATURES:

- base made up of reinforced nylon with fiber glass;
- double pirouetting wheels;
- seat and back of multilayers beech;
- rotation and raising by gas movement;
- articulated back adjustable;
- certified Catas in conformity with European Regulations UNI/8587/84, UNI/8585/84, 9089/87, 8582/84;
- weight: 7,8 Kg.

## MIXER FOR COATINGS, CAST AND PLASTERS



### item: 741/00 - MIXER

The Mixer for coatings, cast and plasters can perform the entire cycle (padding, pouring of the coating, vibration) in vacuum conditions. The incorporated vacuum pump is extremely silent and fitted with an original system for oil recovery and re-circulation which makes it entirely maintenance-free. The padding is obtained by a shielded-poles gear motor that makes the paddle rotate at a speed of 200 rpm. The machine is supplied with a digital electronic Timer that can be used to set the padding time. As the pre-set time elapses (shown on the display), the padding stops and the pouring and vibration can start. During the pouring of the coating, the vibrator can be turned on and the intensity regulated. The machine comes with a complete set of cups in transparent poly-carbonate: 1 cover with paddle, 1 coating cup with regulating tap, 1 cup for plaster, 1 inferior cup, 1 rubber base for cylinder. This vacuum paddle and pouring processing assures excellent results, with compact coatings air bubbles and blowholes free.

**item: 741/20** - Cup capacity 270 cc

**item: 741/21** - Cup capacity 650 cc for plaster

**item: 741/22** - Cup capacity 650 cc for coatings

#### TECHNICAL FEATURES:

Dimensions:	30x42x61 cm
Weight:	35 Kg
Feeding:	220 V - 50 Hz
Power:	500 Watt
Cup capacity:	650 cc
Paddle-mix speed:	200 rpm
Max vacuum:	720 mm/Hg

## PNEUMATIC HAMMER



### item: 745/00 - HAMMER

This instrument allows to smooth away fastly and easily eliminate the undesidered borders of chalk models. The motor of pneumatic functioning, requires a reduced maintenance and it is extremely lasting.

**item: 745/20** - Small spare tool

**item: 745/21** - Medium spare tool

**item: 745/22** - Big spare tool

#### TECHNICAL FEATURES:

Air consumption:	50 lt/min.
Exercise pressure:	from 5 to 7 atm
Weight:	230 gr