



ES-OXY-6SA

Oxygen Concentrator



OPERATING THEATRE



ES-OXY-6SA

Oxygen Concentrator

TECHNICAL SPECIFICATIONS

Flow rate	0-6L/min
Single/Dual Flow Rate	Single Flow
Purity	93 ± 3%
Outlet Pressure (Mpa)	0.04 - 0.07
Nebulizer/Atomization	YES
Sound Level	≤ 50db
Power	AC220V±10%, 50/60±1Hz AC110V±10%, 50/60±1Hz
Power Consumption	≤ 480W
Timer	Present Working Time, Accumulating Time, Presetting Time from 10mins to 40hours
Alarm	Power failure alarm, High & Low pressure alarm
Net Weight	25Kg
Size (mm)	365×375×600mm

Cod. ES-OXY-6SA



OPTIONAL

Low purity alarm: when oxygen purity is above 82%, it will give green light; when the purity is blow 82% (82% not included), it will give red light
Maintenance alarm: alarm for maintenance after 3000 hours operation
Alarm for high temperature inside systems above 50
Pulse oximeter: fingertip pulse oximeter is available for monitoring patient oxygen saturation on site.
Small LCD display: accumulating time; present working time presetting time.



ESSE3 srl, Via Garibaldi 30
14022 Castelnuovo D.B. (AT)
Tel +39 011 99 27 706
Fax +39 011 99 27 506
e-mail esse3@chierinet.it
web: www.esse3-medical.com

